

APPENDIX LIST OF PRODUCTS

Outside Dia	Connection Distance	Nominal Pressure	Dimensions		Distance between Two pipes Rmax.		Connections		
			B	C	Insert	No Insert	Pin	Min.Torq	Maks.Torq
AD (mm.)	Min-Max (mm.)	PN (bar)	Width (mm.)	impermeability distance	(mm.)	(mm.)	(M)	(NM)	(NM)
26.9	26-28	20	56	17	5	5	2xM6	5	18
30.0	29-31	20	56	17	5	5	2xM6	5	18
33.7	33-35	20	56	17	5	5	2xM6	5	18
38.0	38-39	20	76	30	5	10	2xM8	10	52
42.4	42-43	20	76	30	5	10	2xM8	10	52
44.5	44-46	20	76	30	5	10	2xM8	10	52
48.3	47-50	20	76	30	5	10	2xM8	10	52
55.0	54-57	20	76	30	8	15	2xM8	10	52
57.0	56-59	20	76	30	8	15	2xM8	10	52
60.3	59-62	20	76	30	8	15	2xM8	10	52
70.0	69-72	20	105	47	10	28	2xM8	15	52
76.1	76-79	20	105	47	10	28	2xM8	15	52
85.0	84-87	20	105	47	10	28	2xM8	15	52
88.9	88-91	20	105	47	10	28	2xM8	20	52
101.6	101-104	20	105	47	10	28	2xM8	20	52
104.0	104-107	20	105	47	10	28	2xM8	20	52
108.0	108-111	20	105	47	10	28	2xM8	20	52
114.3	113-117	20	105	47	10	28	2xM8	20	52
127.0	125-129	16	120	60	10	30	2xM12	20	143
133.0	132-136	16	120	60	10	30	2xM12	20	143
139.7	138-143	16	120	60	10	30	2xM12	20	143
154.0	152-157	16	120	60	10	30	2xM12	30	143
159.0	157-162	16	120	60	10	30	2xM12	30	143
168.3	167-172	16	120	60	10	30	2xM12	30	143
180.0	178-182	12	152	81	10	30	2xM12	30	143
219.1	218-223	12	152	81	10	30	2xM12	30	143
273.0	272-277	10	152	81	10	30	2xM12	40	143
304.0	301-307	10	152	92	10	30	2xM12	40	143
323.9	323-329	10	152	92	10	35	2xM12	40	143
355.6	352-359	6	152	92	10	35	2xM12	30	143
406.4	402-410	6	152	92	10	35	2XM16	30	346
457.2	452-462	6	152	92	10	35	2XM16	30	346
508.0	503-523	4	152	92	10	35	2XM16	30	346
558.8	554-564	4	152	92	10	35	2XM16	30	346
609.6	604-614	4	152	92	10	35	2XM16	40	346

AD : Out side diameter of the pipe
 B : Width of the roller
 C : Distance between impermeability channels
 Rmax : Distance between two pipes


Hasan HABİBOĞLU
 Surveyor